

Price Computing
Simplified

K I L O T E C H

integrator

Integrator C15 and C30

Designed for any business that sells product by weight. Packed with features that make life simple.



Back

Advantages:

Price computing simplified

- ✓ Easy to use, to train and to program with intuitive Kilotech software

High end features at entry level prices

- ✓ Flexible bar codes in many languages
- ✓ Multiple date formats for USA / Canada (CFIA compliant)

Visible in all lighting conditions


- ✓ The display is visible in direct sunlight, under fluorescent lights or in dim lighting conditions

Portable

- ✓ No need to plug your scale in... comes with a 12 hour rechargeable battery

Two scales in one

- ✓ Multi-interval device – automatically adjusts to give you the graduation and capacity as you need it



Why Legal for Trade Scales Make Good Business Sense

It is a Government requirement that the scale be certified legal for trade when the scale is used to determine pricing in a transaction between the trader and the customer.

In the restaurant and food equipment market, scales are often used to ensure consistency in weight for products sold or used in the preparation of product. Losing even a 1/2 oz. on each measurement could dramatically increase the cost over time to the manufacturer, baker, distributor, vendor, restaurant, etc...

Legal for Trade scales go through a thorough quality inspection, ensuring reliability – you are guaranteed a quality product and peace of mind.



KILOTECH

Loaded with unique features – the best in its class

Scale Features:

- ✓ USB and RS232– easy to connect to your computer for downloading and uploading PLU data
- ✓ Programmable barcode
- ✓ 80 character ingredients field per PLU
- ✓ Multiple date formats for USA/Canada (CFIA compliant)
- ✓ Prepack function comes standard
- ✓ Plug and play printer (optional)
- ✓ NTEP CC 15-060
- ✓ Measurement Canada AM 5987

Model	Integrator C15	Integrator C30
Capacity & Graduation	0 - 6 kg x 0.002 kg / 6 - 15 kg x 0.005 kg 0 - 15 lb x 0.005 lb / 15-30 lb x 0.01 lb	0 - 15 kg x 0.005 kg / 15 - 30 kg x 0.01 kg 0 - 30 lb x 0.01 lb / 30 -60 lb x 0.02 lb
Units of measure	kg, lb	
Direct PLU	5	
Indirect PLU	260	
RS232 for optional printer	Yes	
Operating temperature	0°C – 40°C /50°F - 104°F <60% RH non-condensing	
Power supply	12 VDC 500mA adapter / internal rechargeable battery (12 hours of use between charges)	
Platter Size (D x W)	9.5" x 13.5" (241.3 mm x 342.9 mm)	
Scale Dimensions (W x D x H)	14" x 14.5" x 5" (355.6 mm x 368.3 mm x 127 mm)	

